



- A. This self-adhesive PVC tape is suitable for marking the boundaries of ESD Protected Areas.
- B. It adheres very well to synthetic floors such as PVC tiles.
- C. The tape will also adhere to concrete floors and can be expected to remain intact for several months depending on traffic.
- D. The tape is yellow and printed in black with the ESD logo as per EN 61340-5-1 and the text 'ESD Protected Area'.
- E. The carrier tape is laminated with a clear film to protect the print. The tape is not antistatic as it is intended for use outside the EPA.
- F. The tape is a highly visible identification of the boundaries of an EPA.
- G. Available in two designs.

IEC 61340-5-1 paragraph 5.3.4.1 Handling ESDS and access to EPA
"Handling of ESDS without ESD protective covering or packaging shall be performed in an EPA. The boundaries of the EPA shall be clearly identified as EPA boundaries (e.g. Caution signs indicating the existence of the EPA can be posted and conspicuous to personnel prior to entry to the EPA.)"

Per IEC TR 61340-5-2 paragraph 5.3.3.1 General considerations for EPA
"Some examples of appropriate signs/markings are physical signs, floor tape outlining the border of the EPA, different coloured floor tiles or any other method that defines the border of an EPA."

Item	Description
210300	Floor Marking Tape, 75 mm wide, 33 m long
210310	Floor Marking Tape with Arrows, 50 mm wide, 66 m long

Tolerance ± 5 mm



Made in the United Kingdom

Specifications and procedures subject to change without notice.

Floor Marking Tape

DESCO EUROPE

DESCO EUROPE
 2A DUNHAMS LANE, LETCHWORTH GARDEN CITY,
 HERTFORDSHIRE, SG6 1BE, UK
 PHONE: +44 (0) 1462 672005
 E-MAIL: Service@DescoEurope.com, INTERNET: DescoEurope.com

Drawing Number
 210300

DATE:
 October
 2020